

## Ecoflex® Thermal Twin Jr. with 5.5" Jacket

Submittal Information

Revision A: July 22, 2014

### Project Information

Job Name:

Location: \_\_\_\_\_ Part No. Ordered: \_\_\_\_\_

Engineer: \_\_\_\_\_ Date Submitted: \_\_\_\_\_

Contractor: \_\_\_\_\_ Submitted By: \_\_\_\_\_

Manufacturer's Representative: \_\_\_\_\_ Approved By: \_\_\_\_\_

### Technical Data

**Service Pipe:** Crosslinked polyethylene (PEX) SDR-9 Engel-method tubing that conforms to German DIN 4726; smoothness value of 0.02 mil; NSF-certified

**Insulation:** Multilayered, closed-cell, polyethylene-foam insulation with a thermal conductivity of 0.26 BTU in./sq. ft./hour/°F; vapor permeability of 0.1g/100 sq. in./day

**Jacket:** Corrugated seamless high-density polyethylene (HDPE); UV-protected

**Hydrostatic Ratings:** 200°F (93°C) at 80 psi (551 kPa or 5.51 bar)  
180°F (82°C) at 100 psi (689 kPa or 6.89 bar)  
73.4°F (23°C) at 160 psi (1102 kPa or 11.02 bar)



### Product Information and Application Use

Uponor's Ecoflex® Thermal Twin Jr. is a pre-insulated pipe system for buried or aboveground commercial and residential hydronic radiant heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX) pipe protected by multilayer polyethylene-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with Uponor ProPEX® fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.<sup>1</sup>

✓ Description	Part Number	Service Pipe O.D.	Service Pipe I.D.	Foam Thickness	Insulation Value <sup>2</sup>	Bend Radius	Weight (lbs./ft.)
1¼" Thermal Twin Jr. with 5.5" Jacket, 600-ft. coil	5025513	1.375"	1.054"	0.78"	R-5.09	28"	1.28 lbs.

### Installation

Install Ecoflex Thermal Twin Jr. pre-insulated pipe in buried or aboveground hydronic radiant heating and cooling applications. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid groundwater contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

### Standards

ASTM F876, F877 and F1960; CSA B137.5; NSF/ANSI Standard 14 (NSF-rfh)

### Codes

N/A

### Listings

NSF/ANSI 14-certified

### Related Applications

Pre-insulated Pipe Systems  
Radiant Heating and Cooling Systems  
Snow and Ice Melting Systems  
Permafrost Prevention Systems  
Turf Conditioning Systems

### Contact Information

Uponor, Inc.  
5925 148th Street West  
Apple Valley, MN 55124 USA  
Phone: 800.321.4739  
Fax: 952.891.2008  
www.uponorpro.com

Uponor Ltd.  
2000 Argentia Road, Plaza 1, Suite 200  
Mississauga, ON L5N 1W1 CANADA  
Phone: 888.994.7726  
Fax: 800.638.9517  
www.uponorpro.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.

<sup>2</sup>R-value is normalized based on the nominal foam thickness for a circular shape.